



All dimensions are in mm; tolerances according to ISO 2768 c

**Parts**

Connector 1	DIN male 60S137-C08N1
Cable	1/2" super-flex cable with PE jacket
Bend Protection	Molding
Label	Label Stick

**Available Variants Weight**

Part Number	Customer Number	Length A[mm]	C[mm]	Insertion Loss ≤(dB) at 3.0 GHz	Weight [Gram]
LC08-113-200	N/A	200 ± 5	87 ± 5	0.15	140
LC08-113-500	N/A	500 ± 5	200 ± 10	0.21	180
LC08-113-1000	N/A	1000 ± 10	200 ± 10	0.32	265
LC08-113-1500	N/A	1500 ± 15	200 ± 10	0.43	345
LC08-113-2000	N/A	2000 ± 20	200 ± 10	0.54	425
LC08-113-2500	N/A	2500 ± 25	200 ± 10	0.65	506
LC08-113-3000	N/A	3000 ± 30	200 ± 10	0.76	587
LC08-113-3500	N/A	3500 ± 35	200 ± 10	0.87	667
LC08-113-4000	N/A	4000 ± 40	200 ± 10	0.98	748
LC08-113-5000	N/A	5000 ± 50	200 ± 10	1.20	908
LC08-113-6000	N/A	6000 ± 60	200 ± 10	1.42	1068
LC08-113-7000	N/A	7000 ± 70	200 ± 10	1.64	1228
LC08-113-8000	N/A	8000 ± 80	200 ± 10	1.86	1388
LC08-113-9000	N/A	9000 ± 90	200 ± 10	2.13	1540
LC08-113-10000	N/A	10000 ± 100	200 ± 10	2.49	1708
LC08-113-12000	N/A	12000 ± 120	200 ± 10	2.83	2028
LC08-113-15000	N/A	15000 ± 150	200 ± 10	3.45	2500
LC08-113-18000	N/A	18000 ± 180	200 ± 10	4.20	2988
LC08-113-20000	N/A	20000 ± 200	200 ± 10	4.58	3300

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

LC08-113-30000	N/A	30000 ± 300	200 ± 10	6.77	4900
----------------	-----	-------------	----------	------	------

Nominal values @20°C ambient temperature

**Electrical data**

Impedance	50 Ω
Frequency	DC to 3.0 GHz
Return loss	≤ -28dB DC to 1.0 GHz ≤ -26dB 1.0 to 2.2 GHz ≤ -23dB 2.2 to 3.0 GHz
Insertion loss	See table available variants.
DC breakdown voltage	2500 V rms
Power handling(at 20°C, sea level.VSWR 1.0)	800 W @ 1.0 GHz 500 W @ 2.0 GHz
Intermodulation(3 <sup>rd</sup> Order)	≤ -117 dBm @ 2×20 W@910MHz

**Mechanical data**

Minimum bending radius	
single	25 mm
repeated	35 mm
Max. tensile strength	450N

**Environmental data**

Temperature range	-45 ° C to +85 ° C
Degree of protection (mated pair)	IEC 60529, IP68 (20°C,1m,1.5H)
RoHS	compliant
Notice: The jumper just for indoor application, If for outdoor application, the jumper should be covered with weather proof kits (Mastic tape and electrical tape) at same time.	

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Checker	Approved	Date	Rev.	Engineering change number	Name	Date
Zhukun	20/05/13	Huangh	Heanyang	01/12/15	e	-----	Fuhao	01/12/15